

User:

Thursday, 15/01/2009 11:24:31 AM

Julie Dawson

Process Sheet

Customer

: CU-DAR001 Dart Helicopters Services

Job Number

: 44845 : 12335

Estimate Number P.O. Number

This Issue

: 15/01/2009

: NC

: //

: 41056

S.O. No. :

: PURCHASED PARTS Type

Part Number

Drawing Name

: D30125

: DECAL

Drawing Number

: D3012 REV A : N/A

Project Number

: A **Drawing Revision**

Material

Due Date : 30/01/2009

Qty:

10 Um: Each

Written By

Previous Run

Prsht Rev.

First Issue

Checked & Approved By Comment

: Rev A 01.04.06 New Issue EC

Additional Product

Job Number:



Seq. #:

Machine Or Operation:

Description:

1.0

PG

PURCHASING



Comment: PURCHASING

C209/01/16

Make as per Dwg D3012

Manufacture from 3M 7mil masking film p/n 8522CP

Material release note is required

2.0

D30125P

Decal



Comment: Qty.:

1.0000 Each(s)/Unit

Total: 10.0000 Each(s)

Decal

3.0

PACKAGING 1

PACKAGING RESOURCE #1





Comment: PACKAGING RESOURCE #1

Recieive & Inspect for Transit Damage

Ensure Material Release Note is attached

4.0 QC6



DIMENSIONAL CHECK

5.0

PACKAGING 1



Comment: DIMENSIONAL CHECK

PACKAGING RESOURCE #1





Comment: PACKAGING RESOURCE #1

Identify and Stock

Location:

Dart Aerospace Ltd

W/O:			WC	ORK ORDER CHANG	ES					
DATE STEP		PRO	OCEDURE CHA	NGE	В	y	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
										·
Part No		PAR #:	Fault Cate	gory:	_ NCR: `	es N	lo DQ .	A:	Date:	
	Res	olution:	Dispositio	n:	QA: N/	C Clo	sed:		Date: _	
NCR:		,	WORK ORD	ER NON-CONFORMA	ANCE (I	ICR)	١			
DATE	STEP	Description of NC		Corrective Action Section			Verific	ation	Approval	Approval
DATE	SIEP	Section A	Initial Chief Eng	Action Description Chief Eng		gn & Date	Verification Section C	Chief Eng	QC Inspector	
	!									
				 						
									1	
										

NOTE: Date & initial all entries

Date: User: Thursday, 15/01/2009 11:24:31 AM

Julie Dawson

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: DECAL

Job Number: 44845

Part Number: D30125

Job Number:



Seq. #:

Machine Or Operation:

Description:

6.0

QC21



FINAL INSPECTION/W/O RELEASE

Comment: FINAL INSPECTION/W/O RELEASE

Job Completion



Dart Aerospace Ltd

W/O:			W	ORK ORDER CHANC	GES		• • • • • • • • • • • • • • • • • • • •			
DATE STEP		PRO	OCEDURE CHA	NGE	Ву	,	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

	:									
77.0				·			,	1		
Part No	:	PAR #:	Fault Cate	egory:	_ NCR: Y	es N	o DQ	4 :	_ Date: _	
	R	esolution:	Disposition	on:	QA: N/0	Clos	ed:		Date: _	
NCR:			WORK ORD	ER NON-CONFORM	ANCE (N	CR)				
DATE	STEP	Description of NC			ction B			ation		Approval
	0.2.	Section A	Initial Chief Eng	Action Description Chief Eng		gn & ate	Secti	on C	Chief Eng	QC Inspector
										į
		;								
									:	

NOTE: Date & initial all entries





DESIG	P	DRAWN BY	DART AEROSP, HAWKESBURY, ONTARI	
CHECK	(ED	APPROVED	DRAWING NO.	REV. A
	W	#	D3012	SHEET 1 OF 1
DATE			TITLE	SCALE
01.0	3.30		DECAL	
Α		01.03.30	NEW ISSUE	



- POINT A -SWL=300lb/136kg DO NOT USE WITH POINT B P/N D3012-1

D3012-1

- POINT B -SWL=500lb/227kg DO NOT USE WITH POINT A OR C P/N D3012-3

D3012-3

- POINT C -SWL=300lb/136kg DO NOT USE WITH POINT B P/N D3012-5

D3012-5

SHOP COPY RETURN TO **ENGINEERING** UNCONTROLLED COPY SUBJECT TO AMENDMENT WITHOUT NOTICE

MANUFACTURED FROM 3M 7 MIL MASKING FILM #8522CP WORK ORDER MATERIAL: WHITE LETTERS ON BLACK ADHESIVE BACK

Copyright © 2001 by DART AEROSPACE LTD

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.



210 MAIN W., HAWKESBURY, ONT. K6A 2H6

Tel.: 613 632-5449 Fax: 613 632-9491

www.studiolettrage.on.ca

INVOICE / FACTURE

11600

01/23/2009

No.:

. 1 of 1

Re: Quote No. 6353

PAGE

VENDU À: SOLD TO:

Dart Aerospace Ltd 1270 Aberdeen Hawkesbury, Ontario K6A 1K7 LIVRÉ À: DSHIPPEPATO:td

Hawkesbury, Ontario

	OTV.		and the second s		16	<u> </u>	E0 00
AR ICLE	QTY QYÉ	UNIT UNITE	DESCRIPTION	F 5	PST TVP	UNIT PRICE PRIX UNITÉ	TRUCMA TRATROM
; ;	1	6 10 10 10	D34993 Solor D30121P set up D30125P set up D30125P set up printing	G G G		5.0000 5.0000 50.0000	50.00 50.00
			G - GST @ 5%; PST @ 8% GST				12.50
:			PST Exempt: #6122-5207				
						5 .	
		×					
-						-	
		·		÷			
		1			,		
1		7	Marin Land			₹ å	
Studio de Lett	rage GS	T: #869034678RP00	GST/TPS: R122278690				262.
PO 7992 Sold By:	<u> </u>					TOTAL	

Product Bulletin 8522

3M

Release F, Effective January 2003 Black bar in margin indicates a change

Scotchcal [™] Opaque Imaging Media 8522

Description

This media is specially formulated to dry quickly after printing. Production of outdoor weatherable and long-term indoor durable graphics is now easier than ever. Its changeable adhesive allows easy removal for up to one year.

Advantages

- Optimized for use with selected Epson Stylus Pro printers and Epson Archival inks.
- Optimized for use with selected HP DesignJet Printers and HP DesignJet Ink System UV or HP83UV Color Ink System
- For making opaque, laminated graphics that are outdoor weatherable and long-term indoor durable
- Media:
 - For opaque (reflective) graphics
 - Changeable, easy to remove from warranted substrates up to 1 year later
 - Dries quickly after printing so the overlaminate can be applied almost immediately
 - Low slippage paper liner for superior tiling
- Overlaminates:
 - Provide additional UV (ultraviolet) and physical protection for making weatherable finished graphics
 - Available in luster and matte gloss
 - Adhesive allows for heat-assisted or cold-temperature lamination

Applications and Uses

3M Scotchcal Changeable Opaque Imaging Media 8522 is intended only for ink jet printing and for use with the listed Compatible Products and Equipment and the following applications. Any other application is NOT warranted by 3M or covered by the worldwide 3M MCS Warranty unless 3M gives its prior written approval for the application.

- First surface images (the image is on top of the film) for opaque posters and signs, including:
 - Graphics for vans, personal vehicles, trucks and buses
 - Novelty posters
 - Retail and point-of-purchase displays
 - Information graphics such as maps and directories
 - Entertainment promotions in museums, zoos, parks, theatres, sports venues
 - Education and presentation graphics

- Legal and courtroom exhibits
- For flat or simple curved surfaces, with or without rivers, used in vertical (± 10°) applications

Limitations of End Uses

The following uses and applications are specifically NOT warranted.

- Fleet applications in areas that use salt for winter road
 maintenance
- Application to non-warranted substrates, including wallboard
- · Applications subjected to gasoline vapors or spills
- Application to corrugated or highly irregular surfaces or sharply raised areas
- Graphics applied to stainless steel, including stainless steel vehicles
- On flat surfaces with rivets, tenting of 4 to 10 mm around rivets may be expected; rivets may be cut around to eliminate tenting.

Note: Standard ink jet technology is water based. Water-based chemistry is susceptible to the extremes of heat and humidity. This is a factor in most product constructions on the market. Read the Fabrication. Shelf Life and Storage sections in this bulletin. Staying in the middle of these ranges always provides optimum performance.

Compatible Products and Equipment

Thermal Ink Jet Printing Systems

- Epson Stylus Pro 9500, Stylus Pro 10000 printer
 - Epson Archival Inks
- Epson Stylus Pro 10600 printer
 - Epson Archival Inks
- HP DesignJet Printers 2000 and 3000 series
 - HP DesignJet Ink System UV (pigment-based ink)
- HP DesignJet Printers 5000 series
 - HP83UV Color Ink System

Overlaminates (required)

- 3M[™] Luster Overlaminate 8519 (semi-gloss)
- 3M[™] Matte Overlaminate 8520

Note: For the full product names of the 3M products listed on this page, please see page 1.

Warranted Substrates

Media 8522 is warranted for use on the following rigid substrates.

Some substrates may "out-gas", resulting in tiny bubbles throughout the surface of the graphic. For maximum performance, be sure the substrate you select is properly cleaned and prepared as recommended by the manufacturer. See Instruction Bulletin 5.1 for additional information.

- Alodine (anodized aluminum)
- Automotive panels (automotive painted steel)
- Fruehauf (painted aluminum)
- FRP (fiberglass reinforced plywood)
- Imron® (polyurethane-painted metal panel)
- Acrylic
- Sintra * board

Test and Approve Non-warranted Substrates Before Use

Media 8522 is not warranted for any substrate other than those listed above. If you want to use it for other substrates, 3M recommends that you test and approve the media for both adhesion and removal characteristics.

Characteristics

Characteristic	Description
Media	7 mil, white, opaque graphic film
Liner	Low-slippage, lay flat paper
Adhesive	Changeable, pressure sensitive
Thickness (media and adhesive)	7.5 to 8 mil (nominal)
Application substrates	See Warranted Substrates, above
Application surfaces	Flat or simple curved surfaces, with or without rivets, used in vertical (± 10°) applications (no corrugations)
Application temperature range	28° to 110°F (-2° to 43°C) (air and surface)
Roll sizes	36" x 45 feet (914 mm x 13.5 m) 54" x 45 feet (1372 mm x 13.5 m)

How to Become a 3M Ink Jet Registered Fabricator

Only 3M Thermal Ink Jet Registered Fabricators are eligible to offer 3M MCS warranted graphics. In order to become certified, a fabricator must complete the requirements as specified in the 3M Ink Jet Graphics Registered Fabricator Reference Manual located on the 3M website at www. scotchprint.com

Effective Performance Life

To obtain the warranty given below, the graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3. Also see the section, Removability.

Warranted Durability

Media 8522	Epson Pr	on Printers HP Printe			
with Overlaminate 8519 or 8520	Outdoor	Indoor	Outdoor	Indoor	
Applied to Warranted Substrates	2 years	5 years	3 years	5 years	

Removability

Imaging media 8522 is removable from warranted substrates for 1 year without the aid of chemical strippers or accessories. Refer to Instruction Bulletin 4.23 for additional information.

Fabrication

Graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3.

See Instruction Bulletin 4.23 for detailed fabrication, printing and mounting information.

Graphic Construction Options

Opaque (Reflective) Graphics

Opaque graphics made with imaging media 8522 require an overlaminate and an opaque substrate.

Viewer/Light Source	
	Overlaminate 8519, 8520 Adhesive on bottom
	Imaging Media 8522 Image on top; adhesive on botto
	Opaque Substrate

Note: For the full product names of the 3M products listed on this page, please see page 1.

Shelf Life and Storage

- 3M * Scotchcal * Changeable Opaque Imaging Media 8522 has a shelf life of one year.
- Storage conditions (new and partially used rolls). For optimum performance, use the middle of these ranges:
 - Original packaging, including plastic wrap
 - Relative humidity of 20% to 80%
 - Temperature of 33° to $104^{\circ}F$ (0° to $40^{\circ}C$)
 - Away from direct sunlight
- Do not stack unprotected rolls or lay sharp or heavy objects on them.

Health and Safety

When handling any chemical products, read the manufacturers' container labels and the Material Safety Data Sheets (MSDS) for important health, safety and environmental information.

To obtain MSDS sheets for 3M products:

- By fax, call 1-800-364-0768 in the US and Canada or 1-650-556-8417 for all other locations.
- Electronically, visit us at http://www.3M.com/msds.
- By mail, or in case of an emergency, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.

Warranty and Limited Remedies

3M MCS Warranty for Graphics Produced on HP DesignJet Printers and Epson Stylus Pro Printers

The following is made in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose: We warrant graphics produced by a 3M Ink Jet Registered Fabricator made with imaging media 8522, printed on an approved HP thermal ink jet printer according to HP's recommendations or Epson Stylus Pro printer according to Epson's recommendations, overlaminated with 8519 or 8520, and applied to a Warranted Substrate according to 3M's recommendations. These

graphics are covered against failure caused by ultraviolet light, temperature extremes, pollution, and other elements.

If a graphic fails to perform in accordance with 3M product specifications within this time frame, 3M will replace the materials at no charge. These remedies are exclusive. In no case shall 3M be liable for any direct, indirect, or consequential damages, including any labor charges.

3M Related Literature

Listed below is related 3M technical literature that may be of interest. You may view and print these Bulletins from our Web site at www.scotchprint.com, or order them via our Faxon-Demand (FOD) system. Call one of these phone numbers to order the desired bulletins, and specify the FOD document number provided in the chart.

United States or Canada: 1-800-364-0768 International: 1-651-732-6506

Subject	Bulletin No.	FOD No.				
Product Bulletins						
3M [∞] Scotchcal [∞] Overlaminate 8519 and 8520	8519/8520	4524				
Instruction Bulletins						
Making thermal ink jet graphics	4.23	6523				
Application, substrate selection, preparation and substrate-specific application techniques						
Warranties						
Worldwide 3M ** MCS * Warranty Packet (includes all Commercial Graphics MCS Warranties)						
Worldwide 3M " MCS " Warranty Overview-Folder						

3M, Scotcheal and MCS are trademarks of 3M, Epson and Stylus Pro are trademarks of Epson. HP and DesignIct are tradenames of Hewlett Packard. Sintra is a trademark of Swiss Aluminum Ltd. Imron is a registered trademark of DuPont in the United States

Bulletin Change Summary

The Epson Stylus Pro Printers 9500, 10000 10600, and Epson Archival Inks have been added to this bulletin. Additional changes resulting from this addition are marked with black bars in the margin.

3M

Commercial Graphics Division

3M Center, Building 220-6W-06 PO Box 33220 St. Paul, MN 55133-3220 USA General Into, 1-800-374-6772 Technical Info, 1-800-328-3908 Fax 1-651-736-4233

3M Canada

P.O. Box 5757 London, Ontario Canada N6A 4T1 1-800-265-1840 Fax 519-452-6245

3M México, S.A. de C.V.

Av. Santa Fe No. 55 Col. Santa Fe, Del. Alvaro Obregón México, D.F. 01240 52-55-52-70-04-00 Fax 52-55-52-70-22-77

3M Puerto Rico, Inc.

Puerto Rico Industrial Park P.O. Box 100 Carolina, PR 00986-0100 787-620-3000 Fax 787-750-3035

Fax on-Demand 1-800-364-0768 US/Canada or 1-654-732-6506 International Fax-on-Demand document, 4506 www.scotchprint.com

©3M 2003. All rights reserved.

Product Bulletin 8522 – 3